



FOR HIGH VOLTAGE:  
 BRN TO P  
 BLK TO 3  
 WHT TO 3  
 RED TO 5

ROTATION: CW LEAD END REVERSIBLE  
 TO REVERSE ROTATION INTERCHANGE BLACK AND RED LEADS.

C 2P DUAL VOLT REV W/CAP & PROT

REFER TO SEIM 24-1

REVISION DESCRIPTION FOR: C8396-07 CHANGED FROM MICROSTATION TO SOLIDEDGE		SCALE: NONE UNITS: INCHES	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED) INCHES: ± .015 mm:	TITLE: DIAGRAM OF CONNECTIONS ISSUED BY: A. SANCHEZ APPROVED BY: J.I. SALAZAR REVISION DATE: 04-OCT-13	NIDEC MOTOR CORPORATION REV. A
MATERIAL:		ANGLE: ±	CODE: D04 DWG. NO.: 744276	SHEET NUMBER: 1 OF 1 DWG. SIZE: B	NIDEC CONFIDENTIAL NIDEC MOTOR CORPORATION 07-Oct-13 MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED