



CONNECTIONS

LOW VOLTAGE

HIGH VOLTAGE



T 4P DUAL VOLTAGE REV W/CAPS & PROT

NOTE:
 SECURE ALL LEADS AT 3:00 OCLOCK
 LOCATION TO PREVENT INTERFERENCE
 WITH MOVING PARTS.

ROTATION:
 CW SWITCH END REVERSIBLE
 TO REVERSE ROTATION, INTERCHANGE
 BLACK AND RED LEADS.

REFER TO SEIM 24-1

REVISION DESCRIPTION FOR: C8396-08		SCALE: NONE	UNITS: IN	TITLE: DIAGRAM OF CONNECTIONS		NIDEC MOTOR CORPORATION	
UPDATED BACKGROUND TO NIDEC		TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		ISSUED BY: A. SANCHEZ		APPROVED BY: J.I. SALAZAR	
MATERIAL:		INCHES	mm	REVISION DATE: 23-SEP-13		REV: A	SHEET NUMBER: 1 OF 1
MUST BE COMPLIANT TO ROHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED		XX = ± .01	.XXX = ± .005	CODE: D04	DWG NO: 748863	DWG SIZE: B	SOLIDEDGE
		ANGLES X° = ±1°					