



NOTES:
 - SECURE ALL LEADS TO PREVENT INTERFERENCE WITH MOVING PARTS.
 - STATOR LEADS TO BE CONNECTED TO TERMINAL BOARD PER ORIENTATION SHOWN TO ENSURE LEADS ARE KEPT FROM BORE.

CONNECTIONS

LOW VOLTAGE	HIGH VOLTAGE
P1 — L1	P1 — L1
P2 —	P2 — INSUL.
T3 —	T3 —
T5 —	T5 —
T2 —	T2 —
T4 — L2	T4 — L2
T8 —	T8 —

ROTATION:
 CCW SWITCH END REVERSIBLE
 TO REVERSE ROTATION INTERCHANGE
 T5 AND T8 LEADS

C 4P DUAL VOLT REV W/CAP & PROT

REVISION DESCRIPTION FOR: MISC	SCALE: FULL	UNITS: IN	TITLE: DIAGRAM OF CONNECTIONS	NIDEC MOTOR CORPORATION
ST10712-00: UPDATED FORMAT.	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		ISSUED BY: R. KING	APPROVED BY: K. POTTER
MATERIAL:	INCHES	MM	REVISION DATE: 12-JUL-12	REV: 1
NIDEC CONFIDENTIAL NIDEC MOTOR CORPORATION 12-JUL-12		ANGLES: X° ± 1°	CODE: D04	DWG NO: 766383
MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/EC AND REGULATION EC 1907/2006 (REACH) AS AMENDED			REV: B	SHEET NUMBER: 1 OF 1
				SIZE: B