



- NOTES:
- 1) PLACE PHASE INSULATION AS SHOWN.
 - 2) ONE THERMOSTAT TO CONTACT M1 & M2 AND ONE THERMOSTAT TO CONTACT M2 & M3.
 - 3) ONE WRAP (MINIMUM) OF LACING OVER EACH THERMOSTAT.

3 PHASE
36 SLOT / 6 POLE
ALL PHASES, 1 COIL (OVER 5 TEETH)

NIDEC CONFIDENTIAL
NIDEC MOTOR CORPORATION 23-Sep-13

REVISION DESCRIPTION FOR: C8396-14	SCALE: NONE	UNITS: IN	TITLE: DIAGRAM OF CONNECTIONS	NIDEC MOTOR CORPORATION
UPDATED BACKGROUND TO NIDEC	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		ISSUED BY: A. SANCHEZ	APPROVED BY: J.I. SALAZAR
MATERIAL:	INCHES: XX = ± .01 .XXX = ± .005	mm	REVISION DATE: 23-SEP-13	REV: B
	ANGLES X° = ± 1°		CODE: D04	DWG NO: 769623
			REV: B	SHEET NUMBER: 1 OF 1
				DWG SIZE: B