



CONNECTIONS

LOW VOLTAGE

HIGH VOLTAGE



T 4P DUAL VOLTAGE REV W/CAPS & NO PROT

REFER TO SEIM 24-1

NOTE:
 SECURE ALL LEADS TO
 PREVENT INTERFERENCE
 WITH MOVING PARTS.

ROTATION:
 CCW SWITCH END REVERSIBLE
 TO REVERSE ROTATION
 INTERCHANGE BLACK AND
 RED LEADS

NIDEC CONFIDENTIAL
 NIDEC MOTOR CORPORATION 20-Sep-13

REVISION DESCRIPTION FOR: C8396-15 CHANGED MARK FROM EMERSON TO NIDEC.	SCALE NONE	UNITS IN	TITLE	NIDEC MOTOR CORPORATION
MATERIAL:	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		DIAGRAM OF CONNECTIONS	
	INCHES	mm	ISSUED BY E. VICENCIO	APPROVED BY J.I. SALAZAR
	XX = ± .01		REVISION DATE 21-SEP-13	
	.XXX = ± .005		CODE D04	DWG NO. 779517
	ANGLES X° = ±1°		REV A	SHEET NUMBER 1 OF 1
MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED			DWG SIZE B	SOLIDEDGE