

BEARING RTD'S

1. THERE ARE QTY-1 OR 2 (4 LEAD) BEARING RTD'S INSTALLED,  
ONE PER BEARING.

A = UPPER/ODE (OPPOSITE DRIVE END)  
B = LOWER/DE (DRIVE END)

BEARING RTD'S

	<u>UPPER/ODE</u>	<u>LOWER/DE</u>
(RED)	A1	B1
(RED)	A1	B1
(WHITE)	A2	B2
(WHITE)	A2	B2

ACCESSORY LISTING
QTY 1 OR 2 BEARING RTD'S (4 LEAD)

<b>ENG. REF.</b>
SAI 628563

REVISION DESCRIPTION FOR: 20078299	REVISION DATE <b>24-OCT-07</b>	SCALE <b>NONE</b>	UNITS
<b>NEW</b>	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		
	<u>INCHES</u>	<u>mm</u>	
MATERIAL: MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC	ANGLES X°= ±1°		
---			

TITLE <b>CUSTOMER CONNECTION DIAGRAM</b>	
ISSUED BY <b>R. KING</b>	APPROVED BY <b>K. POTTER</b>
CODE <b>CDG</b>	DWG NO. <b>0628562</b>

REV -	SHEET NUMBER 1 OF 1	DWG SIZE A