ALT.		
B	787005	A

THERMOSTATS

1. MOTOR IS EQUIPPED WITH QTY-3 (1 PER PHASE) NORMALLY CLOSED THERMOSTATS PER WINDING. THERMOSTATS ARE SET TO OPEN AT HIGH TEMPERATURE.

2. THERMOSTATS MUST NOT BE USED TO SWITCH VOLTAGES EXCEEDING 18 VDC OR 240 VAC.

ACCESSORY LISTING
QTY-3 N.C. THERMOSTATS (HIGH SPEED)
QTY-3 N.C. THERMOSTATS (LOW SPEED)

ALT LET	CHANGE NOTICE NO.	DESCRIPTION OF CHANGE
A	MOD	1-MAY-00 UPDATED
B	MOD	5-JUN-00 DELETED SP HTRS

U.S. ELECTRICAL MOTORS
DIVISION OF EMERSON ELECTRIC CO.
ST. LOUIS, MISSOURI

TITLE: CUSTOMER CONNECTION DIAGRAM

SCALE: NONE | UNITS: IN | MATERIAL: --- | DRWN 1-FEB-90, HMG | RVSD 5-JUN-00, RWK | APPD 5-JUN-00, REP | PART# ----- | FRAME ----- | CSTG# ----- | TYPE -----

SHEET 1 OF 1 | PREFIX CDG | ALT. B | 787005 | A