EFFECTIVE:

15-APR-11

SUPERSEDES:

31-MAR-99


HORIZONTAL MOTORS


FRAME: 320US BASIC TYPE: JAD, JDE PRINT:

07-2055

SHEET:

1 OF 1





ALL DIMENSIONS ARE IN INCHES AND MILLIMETERS

	Α	В	С	D 06	Е	2E ± .03	G	H + .05
IN	15.75	13.75	28.56	8.00	6.25	12.50	.75	.66
MM	400	349	725	203	159	318	19	17
	J	К	N	N-W	0	P ²	Т	U 001
IN	3.19	3.25	3.75	3.25	16.25	16.88	2.50	1.625
MM	81	83	95	83	413	429	64	41.28
	SQ. KEY	V MIN	W	AA	AB	AC	AF	BA ± .09
IN	.375	3.50	.50	2-1/2 NPT	15.50	11.38	4.19	5.25
MM	9.53	89	13		394	289	106	133
	BS	ES MIN						
IN	6.00	2.03						
MM	152	52						

		FRAME	2F ± .03	
	N	324US	10.50	
N	MN	32403	267	
	N	326US	12.00	
N	MN	32003	305	

^{1:} ALL ROUGH CASTING DIMENSIONS MAY VARY .25"

DUE TO CASTING VARIATIONS.
2: LARGEST MOTOR WIDTH
3: TOLERANCES ARE SHOWN IN INCHES.

^{4:} CONDUIT BOX MAY BE LOCATED ON EITHER SIDE OF MOTOR. CONDUIT OPENINGS MAY BE LOCATED IN STEPS OF 90 DEGREES REGARDLESS OF LOCATION. STANDARD AS SHOWN WITH CONDUIT OPENING DOWN.