

EFFECTIVE:
09-MAY-11

HORIZONTAL MOTORS


AUTOMOTIVE DUTY WITH NEMA "C" BRACKET

PRINT:
07-2557

SUPERSEDES:
20-FEB-03

FRAME: 364, 365UC
BASIC TYPE: JAD

SHEET:
1 OF 1



ALL DIMENSIONS ARE IN INCHES AND MILLIMETERS

UNITS	C	P ⁴	T	U -.001	W	AA	AB	AC	AF	AG	AH
IN	33.75	18.56	2.50	2.125	.25	2 1/2 NPT	17.38	12.19	4.19	27.63	6.13
MM	857	471	64	53.98	6		441	310	106	702	156

UNITS	AJ	AK -.005	BB MIN	BC	BD MAX	BF ²	BV	ES MIN	SQ KEY
IN	11.000	12.500	.25	.25	14.00	5/8-11 X .94	12.25	5.00	.500
MM	279.40	317.50	6	6	356		311	127	12.70

TOLERANCES	
FACE RUNOUT	.007 T.I.R.
PERMISSIBLE ECCENTRICITY OF MOUNTING RABBET	.007 T.I.R.
PERMISSIBLE SHAFT RUNOUT	.003 T.I.R.

- 1: ALL ROUGH DIMENSIONS MAY VARY BY .25" DUE TO CASTING AND/OR FABRICATION VARIATIONS.
- 2: TAP SIZE AND BOLT PENETRATION ALLOWANCE.
- 3: ALL TAPPED HOLES ARE UNIFIED NATIONAL COARSE, RIGHT HAND THREAD.
- 4: LARGEST MOTOR WIDTH.

- 5: CONDUIT BOX MAY BE LOCATED ON EITHER SIDE OF MOTOR. CONDUIT OPENINGS MAY BE LOCATED IN STEPS OF 90 DEGREES REGARDLESS OF LOCATION, STANDARD AS SHOWN WITH CONDUIT OPENING DOWN.
- 6: TOLERANCES SHOWN ARE IN INCHES ONLY.
- 7: THIS UNIT MAY HAVE HORIZONTAL LIFTING, VERTICAL LIFTING OR BOTH.

07-2557/A

Nidec Motor Corporation
St. Louis, Missouri

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION



ISSUED BY
R. KING
APPROVED BY
K. POTTER

IHP_DP_NMCA (MAR-2011) SOLIDEDGE