



2 LEADS, #18, .031 THICK INSULATION TO BE TIED TO TERMINAL BOARD AND EXTEND 3.000+2-0 BEYOND MOTOR, THEN COILED INTO A SMALL HANK UNDER TERMINAL COVER AFTER TESTING, LEADS TO BE SKINNED .750±.062

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN	
K55HXNFA-7278	-	USEM	1/2	115	6.4	60	825	CCW LEAD END	1940	
SHEET NUMBER 1 OF 1	REV D	REVISION RECORD FOR: D1446-00			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION				NIDEC MOTOR CORPORATION	
CHANGED POSITION OF WARNING LABEL.										
REVISION DATE 03-JUL-14										
ISSUED BY I. GUTIERREZ	REVIEWED BY J. I. SALAZAR	ENGINEER APPROVED J. I. SALAZAR	TITLE ASSEMBLED VIEW				CODE V01	ITEM NO. 752404	SIZE B	

NIDEC MOTOR CORPORATION 03-Jul-14