



8 LEADS, #18, .062 THICK INSUL.
 TO EXTEND BEYOND MOTOR:
 PUR=6.000±1.000, ORG=6.000±1.000,
 BLU=6.000±1.000, RED=6.000±1.000,
 BRN=6.000±1.000, WHT=6.000±1.000,
 YEL=6.000±1.000, BLK=6.000±1.000.
 TO BE COILED INTO SWITCH BOX AND
 SKINNED .750

CONNECTIONS

| FOR 115 VOLTS | | FOR 230 VOLTS | |
|---------------|----------|---------------|----------|
| BLUE | L1 | BLUE | L1 |
| ORANGE | INSULATE | BROWN | INSULATE |
| BROWN | | WHITE | INSULATE |
| PURPLE | INSULATE | ORANGE | INSULATE |
| RED | | PURPLE | |
| BLACK | L2 | RED | L2 |
| YELLOW | | BLACK | |
| WHITE | | YELLOW | |

NIDEC MOTOR CORPORATION 27-Oct-17

| MODEL | REF | CUSTOMER | HP | VOLTS | AMPS | HZ | RPM | ROTATION | CUSTOMER PN |
|---------------|-----|----------|----|---------|----------|----|------|------------------|-------------|
| T63AVBWY-1126 | | STANDARD | 2 | 115/230 | 19.0/8.5 | 60 | 1725 | CCW LEAD END REV | 7073 |

| SHEET NUMBER | REV | REVISION RECORD FOR: ECO E29756 | |
|---------------|-------------|--|--|
| 1 OF 1 | F | CHANGED VIEW OF GROUND LEAD BEHIND OF THE BASE SWITCH LEAD | |
| REVISION DATE | | | |
| 06-NOV-17 | | | |
| ISSUED BY | REVIEWED BY | ENGINEER APPROVED | |
| C. LUGO | R. CRUZ | B. GAITAN | |

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

NIDEC MOTOR CORPORATION

ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN

| TITLE | CODE | ITEM NO. | SIZE |
|----------------|------|----------|------|
| ASSEMBLED VIEW | V01 | 752659 | A |