


(3) .250 INSULATED STRAIGHT TYPE Q.C. TERMINALS WITH INSUL. GRIP AMP ULTRA POD #521367-2 OR EQUIVALENT

3 LEADS #18, 2/64 THICK INSUL. TO EXTEND THROUGH CONDUIT FITTING:  
 PUR=35.000 +2 -0, BLK=35.000 +2 -0  
 ORG=35.000 +2 -0



MOTOR MOUNTED IN SHAFT-DOWN POSITION

NIDEC MOTOR CORPORATION 13-Nov-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
K55HXDVD-1268	A33545	WHOLESALE-HAC	1/3	208-230	1.7	60	1075	C.C.W. LEAD END	LX7932

SHEET NUMBER	REV	REVISION RECORD FOR: C6402-01
1 OF 1	A	UPDATED ENGINEER APPROVED TO B. GAITAN
REVISION DATE		
13-NOV-12		

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

**NIDEC MOTOR CORPORATION**

ISSUED BY	REVIEWED BY	ENGINEER APPROVED	REV
R. MORALES	M. LARGENT	B. GAITAN	A

TITLE	CODE	ITEM NO.	SIZE
ASSEMBLED VIEW	V01	788943	A