V02 USEM pg 1 English MODEL CUSTOMER **VOLTS** AMPS DESCRIPTION / REMARKS USEM T63BXCPD-2241 1.15 13.2 230 MANUAL N56, ODP, COMPRESSOR 001 D3CPMIT 13.184 3.0 208/230 60 3450 A A **A** ±.060 (6.50)5.900 ±.015 B.C. DIA. -NAMEPLATE -THERMAL PROTECTOR (IF REQUIRED SEE CHART) WARNING LABEL -OPPOSITE SIDE -1.940 ± .031 (1.875)**KEYWAY** .188 X 1.440 TOP (.517)TOP (8.50)3.500 +.000 SHAFT KEY TAPED TO MOTOR **-** (.34) -(1.250) (3.00)1/2 -14 NPSM THREAD WITH CONDUIT PLUG (4.88)MOTOR IS CCW ROTATION LEAD END, TO REVERSE ROTATION INTERCHANGE RED AND BLACK LEADS. REFER TO S.E.I.M. 24-1 NIDEC MOTOR CORPORATION 26-Nov-15 REVISION RECORD FOR: E24399 TOLERANCES ON DIMENSIONS **NIDEC MOTOR CORPORATION** WAS CHANGED DIMENSION TO 5.900 ± .015 (UNLESS OTHERWISE SPECIFIED) REVISION DATE : INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSEDWITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION 26-NOV-15 **INCHES**

CUSTOMER DETAIL DRAWING

V02

807269

 $.XX = \pm .010$ $.XXX = \pm .005$

ANGLES X°= ±1°

T. BOSSALLER

A. DEL ANGEL

SHEET NUMBER

1 OF